

Factory Model	year	identification				specifics feature												warnings
		item kit	RB type	item wiring	exp. cost	O2 mod.	injec.	self adapt.	8 inject.	sw maps	gear read	speed limiter	ignition	engine brake	rpm limiter	quick shifter	s.rod type	
Daytona Triple 675 / R	06->08	KRBEA-020	Easy	F27-EA-020		V												
Daytona Triple 675 / R	06->08	KRBEVO-013B	Evo	F27-ER-013		V	V	V			V	V					V	
Daytona Triple 675 / R	09->12	KRBEA-020	Easy	F27-EA-020		V												
Daytona Triple 675 / R	09->12	KRBEVO-013A	Evo	F27-ER-013		V	V	V			V	V					V	
Daytona Triple 675 / R	13	KRBEA-020	Easy	F27-EA-020		V												
Daytona Triple 675 / R	13	KRBEVO-013C	Evo	F27-ER-013		V	V	V			V	V						WARNING: the quick shifter RB isn't applicable
Speed Triple 1050i / R	05->06	KRBEA-016	Easy	F27-EA-016		V												
Speed Triple 1050i / R	05->06	KRBEVO-036B	Evo	K27C-ER-009		V	V	V									V	
Speed Triple 1050i / R	07->10	KRBEA-020	Easy	F27-EA-020		V												
Speed Triple 1050i / R	07->10	KRBEVO-036	Evo	F27-ER-036		V	V	V									V	
Speed Triple 1050i / R	11->13	KRBEA-020	Easy	F27-EA-020		V												
Speed Triple 1050i / R	11->13	KRBEVO-036C	Evo	F27-ER-036		V	V	V									V	
Street Triple 675 / R	07->13	KRBEA-020	Easy	F27-EA-020		V												
Street Triple 675 / R	07->13	KRBEVO-013	Evo	F27-ER-013		V	V	V			V	V					V	A
Tiger 1050	07->13	KRBEA-020	Easy	F27-EA-020		V												
Tiger 1050	07->13	KRBEVO-036A	Evo	F27-ER-036		V	V	V									V	
Tiger 800	11->13	KRBEA-020	Easy	F27-EA-020		V												
Tiger 800	11->13	KRBEVO-060	Evo	F27-ER-060		V	V	V									V	
Tiger Explorer 1215 / XC	12->13	KRBEVO-075	Evo	F27-ER-075		V	V	V			V						V	

Factory Model year	identification				specifics feature											warnings
	item kit	RB type	item wiring	exp. cost	O2 mod.	injec.	self adapt.	8 inject.	sw maps	gear read	speed limiter	ignition	engine brake	rpm limiter	quick shifter	

RB Evo and Racing additional accessories:

F27ADORI-ER	By-pass adapter to set the bike back to stock conditions.
F27SWMAPS-ER	Handlebar switch (basic model).
F27SWMAPS2-ER	Handlebar switch (black anodized billet aluminum.
F27SWGEAR-ER	Quick-shifter load cell sensor with digital setting.
F27-SW-PB	Quick-shifter button to be mounted on the handlebar.
K27-CAN-001 + C27SONDA	MY TUNING BIKE complete kit for permanent self-remapping with WB O2 sensor via CAN-BUS line.

RB Racing additional accessory:

F27-SW-PIT	Handlebar switch for PIT-LANE rpm limiter activation.
------------	---

Description specific features:

O2 mod.	O2 sensors signal management (reading and modulation);
injec.	Digital "multipoint" fuel management
self adapt.	Auto-adaptive feature for dynamic injection map adjustments based on the stock O2 sensor signal;
8 inject.	Managing all 8 signals coming from the injectors to reach an optimal adjustment of A/F ratio;
sw maps	Multi-maps management (only with handlebar switch connected);
gear read	Reading the sensor gear position signal in order to manage the different cut-off timings with the electronic quick-shifter and for managing a different map for each gear position;
speed limiter	Modifying the gear position setting to stop the activation of speed limiter;
ignition	Spark advance dynamic management;
engine brake	Engine brake management (while decelerating);
rpm limiter	All injectors signal management to extend flow rate over the stock limiter;
quick shifter	Managing engine cut-off for quick-shifting once the optional sensor is connected (SWGEAR or SW-PB);
s.rod type	Shifting rod type specification for stock rear sets;